



- UL, cUL Recognized and CSA Certified
- As per ANSI C57.13 OR IEC 60044 standard
- 100% Routine Test Results
- ISO 9001 & ISO 14001 certified manufacturing facilities

INSULATION LEVEL

600 V, BIL 10kV full wave

FREQUENCY

50-400 Hz

OUTER ENCAPSULATION

Plastic Cased

SECONDARY TERMINALS

Brass screw # 10-32 with one flat washer and lock washer, accessible from either side

APPROX. WEIGHT

30 lbs.

CUSTOM OPTIONS (CONTACT US)

- Different Ratios
- IEC Ratios/Accuracies
- Non-standard thermal rating
- Different encapsulation
- Different secondary termination
- Special mounting needs

TABLES

CATALOG NUMBER	CURRENT RATIO	RELAY CLASS	ANSI METERING CLASS @ 60 HZ					Thermal Rating	
			BO.1	B0.2	B0.5	B0.9	B1.8	30 C	55 C
CT112-500	50:5	C 10	2.4	4.8	-	-	-	2.0	1.5
CT112-750	75:5	C 20	2.4	2.4	4.8	-	-	2.0	1.5
CT112-101	100:5	C 20	1.2	2.4	2.4	4.8	-	2.0	1.5
CT112-151	150:5	C 20	0.6	1.2	1.2	2.4	4.8	2.0	1.5
CT112-201	200:5	C 50	0.6	0.6	1.2	1.2	2.4	2.0	1.5
CT112-251	250:5	C 50	0.3	0.6	0.6	1.2	2.4	2.0	1.5
CT112-301	300:5	C 100	0.3	0.3	0.6	0.6	1.2	2.0	1.5
CT112-401	400:5	C 100	0.3	0.3	0.3	0.3	0.6	2.0	1.5
CT112-501	500:5	C 100	0.3	0.3	0.3	0.3	0.6	2.0	1.5
CT112-601	600:5	C 200	0.3	0.3	0.3	0.3	0.3	2.0	1.5
CT112-751	750:5	C 200	0.3	0.3	0.3	0.3	0.3	2.0	1.5
CT112-801	800:5	C 200	0.3	0.3	0.3	0.3	0.3	2.0	1.5
CT112-102	1000:5	C 200	0.3	0.3	0.3	0.3	0.3	2.0	1.5
CT112-122	1200:5	C 400	0.3	0.3	0.3	0.3	0.3	2.0	1.5
CT112-152	1500:5	C 400	0.3	0.3	0.3	0.3	0.3	2.0	1.5
CT112-202	2000:5	C 400	0.3	0.3	0.3	0.3	0.3	2.0	1.5
CT112-252	2500:5	C 400	0.3	0.3	0.3	0.3	0.3	1.33	1.0
CT112-302	3000:5	C 400	0.3	0.3	0.3	0.3	0.3	1.33	1.0
CT112-402	4000:5	C 400	0.3	0.3	0.3	0.3	0.3	1.33	1.0
CT112-502	5000:5	C 400	0.3	0.3	0.3	0.3	0.3	1.0	0.8

DIMENSIONS (ALL DIMENSIONS ARE IN INCHES):

